

ASSEMBLY INSTRUCTIONS

JUMBO BASE STABILIZER

JUMBO Base Stabilizer is universal and fits **JUMBO** Super Proff plain, extension and combi ladders. The base stabilizer is available in two variants: 100 cm base stabilizer, art.no. 41JSF100 - recommended for **JUMBO** Super Proff ladders up to 6 m length. 125 cm base stabilizer, art.no. 41JSF125 - recommended for **JUMBO** Super Proff ladders in all lengths.



JUMBO Base Stabilizer must always be mounted at the bottom of the ladder and into the predrilled holes. On ladders with multiple joints (eg. extension and combi ladders) the base stabilizer should be mounted on the bottom ladder - that is, the widest ladder part.



1 Start by loosening the two bolts at the bottom of each ladder stile.

Remove the bolts on the inside of the stile, but allow the outside counterpart to stay put.



Loosen the bolts on the brackets of the base stabilizer slightly so the brackets can easily slide back and forth.



2 Now mount the base stabilizer so the ladder's rubber feet rest onto the base stabilizer.

The brackets on the base stabilizer should be mounted on the inside of the ladder stiles. Fasten the brackets with the bolts that were removed in step 1.

Do not tighten the bolts completely yet.



3 Now the base stabilizer must be centered. This is done by sliding the base stabilizer sideways in the brackets until the label for center indication is centered to the ladder itself.

When the base stabilizer is centered all bolts on both stiles of the ladder as well as those on the base stabilizer must be securely tightened. The ladder is now ready for use.

Remember to inspect your ladder and accessories regularly.

